ICASE

STABLE FINITE ELEMENTS

FOR THE NAVIER-STOKES EQUATIONS

G. J. Fix

D. N. Lee

and

G. Liang

Report No. 81-37

November 19, 1981

Stable Finite Elements

for the Navier-Stokes Equations

G. J. Fix
Carnegie-Mellon University

D. N. Lee
Carnegie-Mellon University

G. Liang
Carnegie-Mellon University

ABSTRACT

The use of arbitrary spaces to represent the velocities and pressures

in the Navier-Stokes equations typically leads to unstable finite element

approximations. We show in this paper that if spaces of piecewise poly-

nomial functions are used and if the grid for the velocity field is suffi-

ciently fine compared to the grid for the pressure, then the resulting

finite element approximations are stable and converge at the optimal rates.

1.   Introduction

This paper is concerned with the identification of finite element spaces which yield stable and convergent approximations to the Navier-Stokes equations. It has been known for several years that the selection of arbitrary finite element spaces will typically lead to instabilities in the pressure ([2], [5], [6], [8]). Only special choices will work. This is analogous to the situation that exists with finite difference approximations, where only specially constructed schemes will be stable.

Previous work has identified a number of special spaces which yield stable approximations. For example, in the planar case it has been shown [6] that if the space of velocities consist of continuous piecewise quadratic function and piecewise constant representations are used for the pressure, then the resulting finite element scheme is stable. A similar result holds if the space of velocities consist of continuous piecewise linear functions augmented by suitable trilinear functions. These results do require that the grid be regular and satisfy an angle condition, but there are no other restrictions on the shape of the elements. On the other hand, for specially shaped elements such as the crisscross pattern the smaller space consisting only of continuous piecewise linear functions is stable [3].

The work contained in this paper is an extension of first type of element cited above in the sense that there are no restrictions on the shape of the elements. In particular, we show that the finite element scheme is stable provided that the dimension of the space of velocities is sufficiently large compared to the dimension of the space of pressures. This can readily be translated into a mesh ratio condition which is familiar from previous work on hybrid finite methods [4].

In this last section we show that similar results also apply to the Poisson equation when written as a first order system.

2. The Brezzi Condition

Let Ω be a bounded region in $\mathbb{R}^n$ ($n = 2$ or 3). We consider an incompressible flow in Ω where $\underset{\sim}{u}$ denotes the velocity, p the pressure, $\underset{\sim}{f}$ the body forces, and ν and the viscosity. We shall be interested in the nonlinear case where the equations of motions take the form

$$(2.1) \qquad -\nu \Delta \underset{\sim}{u} + (\underset{\sim}{u}\cdot\text{grad})\underset{\sim}{u} + \text{grad}\,p = \underset{\sim}{f} \quad \text{in } \Omega \quad ,$$

$$(2.2) \qquad \text{div}\,\underset{\sim}{u} = 0 \quad \text{in} \qquad ,$$

$$(2.3) \qquad \underset{\sim}{u} = \underset{\sim}{0} \quad \text{on } \partial\Omega \quad .$$

It is known that $(2.1) - (2.3)$ has a unique solution provided the generalized Reynolds number [6] is sufficiently small. We shall assume this without further comment in the sequel. We shall also be interested in the linear case where the term $\underset{\sim}{u}\cdot\text{grad}$ is replaced with $\underset{\sim}{\hat{u}}\cdot\text{grad}$ for some known divergent free velocity field $\underset{\sim}{\hat{u}}$. In the latter case the restriction on the Reynolds number is not needed.

To define the approximation procedure we let

$$(2.4) \qquad \vec{H}_0^1(\Omega) = \{\underset{\sim}{v} : \text{grad}\,\underset{\sim}{v} \in L^2(\Omega), \ \underset{\sim}{v} = \underset{\sim}{0} \ \text{on } \partial\Omega\},$$

and

$$(2.5) \qquad L_0^2(\Omega) = \{q : q \in L^2(\Omega), \int_\Omega q = 0\}.$$

We select two finite dimensional subspaces

$$(2.6) \qquad \vec{V}_h \subseteq H_0^1(\Omega), \qquad S_H \subseteq L_0^2(\Omega),$$

and seek a pair

(2.7) $\qquad \underline{u}_h \in \vec{V}_h, \qquad p_H \in S_H$,

such that

(2.8) $\quad \int_\Omega \{\text{grad } \underline{u}_h \cdot \text{grad } \underline{v}^h + (\underline{u}_h \cdot \text{grad } \underline{u}_h) \cdot \underline{v}^h\} - \int_\Omega p_H \text{ div } \underline{v}^h = \int_\Omega \underline{f} \cdot \underline{v}^h$,

(2.9) $\qquad\qquad\qquad\qquad\qquad \int_\Omega q^H \text{ div } \underline{u}_h = 0$,

holds for all $\underline{v}^h$ in $\vec{V}_h$ and q^H in S_H. Once a basis has been chosen for $\vec{V}_h$ and S_H, the above reduces to a set of nonlinear algebraic equations [3].

As noted in the introduction this system will in general be unstable, and only special choices for $\vec{V}_h$ and S_H will lead to convergent approxi-mations. The condition for stability was first formulated by Brezzi [1], and it takes the following form (see also [2] for an alternate but in this context equivalent formulation):

(2.10) $\qquad\qquad\qquad \sup\{\int_\Omega q_H \text{ div } \underline{v}^h\} \geq \beta\|q_H\|_0^{(1)}$.

Here the sup is taken over all $\underline{v}^h$ in $\vec{V}_h$ with

$$\|\underline{v}^h\|_1 \leq 1,$$

and q_H is any element in S_H. The number β should satisfy $0 < \beta < \infty$ and should be independent of q_H. In addition, it should be bounded away from zero as the dimension of the spaces $\vec{V}_h \times S_H$ approaches infinity.

---

(1) In the sequel we shall use standard Sobolev space notation with $\|\cdot\|_r$ denoting the norm on $H^r(\Omega)$ or $\vec{H}^r(\Omega)$.

3. A Class of Finite Element Spaces

We are now prepared to state and prove our main result. Here we assume that $\vec{V}_h$ and S_H are finite element spaces with h and H being mesh spacings. It is assumed that these spaces have the standard approximation properties; i.e.,

$$(3.1) \qquad \inf \| \underline{u} - \underline{v}^h \|_1 \; \leq \; C_A h^{k-1} \| \underline{u} \|_k \; ,$$

$$(3.2) \qquad \inf \| p - g^h \|_0 \; \leq \; C_A H^\ell \| p \|_\ell \quad ,$$

for suitable integrals $1 < k \leq K$, $1 \leq \ell \leq L$, and for a positive constant C_A independent of h, H, $\underline{u}$ and p.

For spaces S_H of piecewise polynomial functions we have

$$(3.3) \qquad S_H \subseteq \dot{H}^\varepsilon(\Omega),$$

for some $\varepsilon > 0$. For example, if S_H consists of discontinuous piecewise polynomial functions (such as piecewise constants), then ε can be any number in the range $0 < \varepsilon < \frac{1}{2}$. In addition, if the grid for S_H is quasi-regular, then an inverse property is valid. More precisely, there is a number $0 < C_I < \infty$ independent of H such that

$$(3.4) \qquad \| q_H \|_\varepsilon \; \leq \; C_I H^{-\varepsilon} \| q_H \|_0 ,$$

holds for all q_H in S_H.

Theorem 1. _Let (3.1) - (3.4) hold. Then there is a constant_ C _independent of_ H, h, u, _and_ p _such that if_

$$(3.5) \qquad Ch/H \; < \; 1,$$

then the Brezzi condition (2.10) is valid.

Remark. In short this result states that the approximation will be stable provided the <u>mesh spacing</u> <u>h</u> <u>for</u> <u>the</u> <u>velocities</u> is <u>sufficiently</u> <u>fine</u> compared to the <u>mesh spacing</u> <u>H</u> <u>for</u> <u>the pressure</u>. The condition (3.5) is familiar from other results on mixed and hybrid finite element methods [4].

The starting point in the proof of Theorem 1 is a result due to Leray which in effort states that the Brezzi condition (2.10) is valid in the infinite dimensional case where $\vec{V}_h$ is replaced with $H_0^1(\Omega)$ and S_H is replaced by $L_0^2(\Omega)$. It is normally stated in the context of the ability to stably decompose a vector field into a divergence free part plus a curl free part. Here we give an equivalent form the proof of which can be found in [7].

__Theorem 2: Leray.__ _Let_ $f \in L_0^2(\Omega)$. _Then there is a_ $\underline{v} \in \vec{H}^2(\Omega)$ _such that_

$$(3.6) \qquad \operatorname{div} \underline{v} = f \quad \text{in} \quad \Omega \,,$$

$$(3.7) \qquad \underline{v} = \underline{0} \quad \text{on} \quad \partial\Omega \,,$$

with

$$(3.8) \qquad \|\underline{v}\|_1 \leq c_L \|f\|_0 \,,$$

where $0 < c_L < \infty$ _is a constant independent of_ f _and_ $\underline{v}$.

Strictly speaking, the result is valid only for smooth regions Ω that for example are free of re-entrant corners such as convex regions or regions with C^∞ boundaries. In such cases, the smoothness of $\underline{v}$ increases with the smoothness of f. In particular, we have the following

Corollary. Let $f \in H^{\delta}(\Omega) \cap L_0^2(\Omega)$. Then there is a $v \in \vec{H}^{1+\delta}(\Omega)$ satisfying (3.5) – (3.6) and

$$(3.9) \qquad \|\underline{v}\|_{1+\delta} \ \leq\ C_L \|p\|_{\delta} \ ,$$

for $0 \leq \delta \leq 1$.

We are now prepared to prove Theorem 1. To do this we must show there is a number β such that for any q_H in S_H we have

$$(3.10) \qquad \int_{\Omega} \{q_H \ \mathrm{div} \ \underline{v}_h\} \ \geq\ \beta \|q_H\|_0 \ \|\underline{v}_h\|_1 \ ,$$

for a suitable $\underline{v}_h$ in $\vec{V}_h$. Let $\underline{v}$ satisfy

$$(3.11) \qquad \mathrm{div} \ \underline{v} \ = \ q_H \quad \mathrm{in} \ \Omega,$$

$$(3.12) \qquad v \ = \ 0 \quad \mathrm{on} \ \Gamma \ ,$$

with

$$(3.13) \qquad \|v\|_{1+\varepsilon} \ \leq\ C_L \|q_H\|_{\varepsilon} \ .$$

where C_L is the constant in Theorem 2. Using the approximation property (3.1) we select $\underline{v}_h$ in $\vec{V}_h$ satisfying

$$(3.14) \qquad \|\underline{v} - \underline{v}_h\|_1 \ \leq\ C_A h^{\varepsilon} \|\underline{v}\|_{1+\varepsilon} \ \leq\ C_A C_L h^{\varepsilon} \|q_H\|_{\varepsilon} \ .$$

Using the inverse property (3.4) this becomes

$$(3.15) \qquad \|\underline{v} - \underline{v}_h\|_1 \ \leq\ C_* (h/H)^{\varepsilon} \|q_H\|_0 \ .$$

where

$$(3.16) \qquad C_* \ = \ C_A C_L C_I.$$

Since $\text{div } \underline{v} = q_H$ we also have

(3.17)
$$\| q_H \|_0 \leq \| \underline{v} \|_1 .$$

Hence (3.15) implies

(3.18)
$$\| \underline{v} - \underline{v}_h \|_1 \leq C_*(h/H)^\varepsilon \| \underline{v} \|_1 .$$

We now put these inequalities together to establish (3.10). Indeed, first note that

$$\int_\Omega \{ q_H \text{ div } \underline{v} \} = \| q_H \|_0^2 \geq C_L^{-1} \| q_H \|_0 \| \underline{v} \|_1 .$$

Thus, using (3.18) we have

$$\int_\Omega \{ q_H \text{ div } \underline{v}_h \} = \{ q_H \text{ div } \underline{v} \} - \{ q_H \text{ div } (\underline{v} - \underline{v}_h) \}$$

$$\geq (C_L^{-1} - C_*(h/H)^\varepsilon) \| q_H \|_0 \| \underline{v} \|_1 .$$

But

$$\| \underline{v}_h \|_1 - \| \underline{v} \|_1 \leq \| \underline{v} - \underline{v}_h \|_1 \leq C_*(h/H)^\varepsilon \| v \|_1 .$$

Thus

$$\int_\Omega q_H \text{ div } \underline{v}_h \geq (1 + C_*(h/H)^\varepsilon)^{-1} (C_L^{-1} - C_*(h/H)^\varepsilon) \| q_H \|_0 \| \underline{v}_h \|_1 .$$

Thus, (3.10) holds with

$$\underline{\beta} = (1 + C_*(h/H)^\varepsilon)^{-1} (C_L^{-1} - C_*(h/H)^\varepsilon) .$$

It follows that $\underline{\beta}$ is bounded above from zero as $h, H \to 0$ provided h/H is sufficiently small. In particular, the constant C in Theorem 1 is

$$C = (C_* C_L)^{1/\varepsilon} = (C_L^2 C_A C_I)^{1/\varepsilon} .$$

4.   The Poisson Equation

We now consider the Poisson equation which we write in first order form as follows:

$$(4.1) \qquad \underline{u} - \text{grad } \phi = 0 \quad \text{in} \quad \Omega \ ,$$

$$(4.2) \qquad \text{div } \underline{u} = f \quad \text{in} \quad \Omega \ ,$$

$$(4.3) \qquad \phi = g \quad \text{on} \quad \partial\Gamma \ .$$

The weak form of this system is to seek

$$(4.4) \qquad \underline{u} \in H(\text{div},\Omega) = \{\underline{v} \in L^2(\Omega) : \text{div } \underline{v} \in L^2(\Omega)\} \ ,$$

$$(4.5) \qquad \phi \in L^2(\Omega),$$

such that

$$(4.6) \qquad \int_\Omega \underline{u} \cdot \underline{v} + \int_\Omega \phi \ \text{div } \underline{v} = \int_\Gamma g \, \underline{v} \cdot \underline{\nu} \ ,$$

$$(4.7) \qquad \int_\Omega \phi \, \text{div } \underline{u} = \int_\Omega \psi \, f \ ,$$

holds for all $\underline{v} \in H(\Omega:\text{div})$ and $\psi \in L^2(\Omega)$. In (4.6) $\underline{\nu}$ denotes the outer normal to Ω.

As with the Navier-Stokes equations are approximate procedure is obtained by first introducing finite dimensional subspaces

$$\vec{V}_h \subseteq H(\Omega,\text{div}), \ S_H \subseteq L^2(\Omega).$$

One then seeks

$$\underline{u}_h \in \vec{V}_h, \quad \phi_H \in S_H,$$

such that (4.6) - (4.7) holds with $\underline{u}$ replaced with $\underline{u}_h$ and ϕ replaced with ϕ_H. In addition, $\underline{v}$ and ψ are restricted to V_h and S_h, respectively.

The stability and convergence of this scheme centers on a condition similar to (2.10) which was formulated in [5]. In particular, there must be an absolute number $0 < \beta < \infty$ for which

$$(4.8) \qquad \sup(\underline{v}^h, q_H)_{-1} \geq \beta \| q_H \|_{-1} .$$

Here $(\cdot, \cdot)_{-1}$, $\| \cdot \|_{-1}$ denote the inner product and norm on $H^{-1}(\Omega)$, and the sup is taken over all $\underline{v}^h$ in $\vec{V}_h$ with

$$(4.9) \qquad \| \underline{v}^h \|_0 \leq 1.$$

We now show that the analog of Theorem 1 is valid.

Theorem 3. *Let the assumptions in Theorem 1 hold. Then (4.8) is valid.*

The following is a special case of Theorem 2 and its Corollary.

Lemma. *Let $f \in H^0(\Omega)$. Then there is a $\underline{v} \in H^1(\Omega)$ such that*

$$(4.8) \qquad \operatorname{div} \underline{v} = f \quad \text{in } \Omega.$$

Moreover,

$$\| \underline{v} \|_{1+\delta} \leq c \| f \|_\delta ,$$

for $-1 \leq \delta \leq 1$.

To prove (4.8) we let

$$\operatorname{div} \underline{v} = q_H .$$

Then

$$(4.9) \qquad (\text{div}\,\underline{v},\ q_H)_{-1} = \|q_H\|_{-1}^2 \geq (1/C)\|q_H\|_{-1}\|\underline{v}\|_0 .$$

We now select a $\underline{v}_h \in \vec{V}_h$ such that

$$\|\underline{v} - \underline{v}_h\|_0 \leq Ch^\varepsilon \|\underline{v}\|_\varepsilon \leq Ch^\varepsilon \|q_H\|_{-1+\varepsilon} .$$

Using the inverse inequality

$$\|q_H\|_{-1+\varepsilon} \leq H^{-\varepsilon}\|q_H\|_{-1} .$$

We obtain

$$(4.10) \qquad \|\underline{v} - \underline{v}_h\|_0 \leq C(h/H)^\varepsilon \|q_H\|_{-1} .$$

Thus (as in section 3) we obtain

$$(4.11) \qquad (\text{div}\,\underline{v}_h,\ q_H)_{-1} \geq (C_1 - C_2(h/H)^\varepsilon)\, \|q_H\|_{-1}\|\underline{v}_h\|_0 ,$$

for absolute positive constants C_1 and C_2.

References

[1] Brezzi, F.: On the existence, uniqueness and approximation of saddle point problems arising from Lagrangian multipliers. RAIRO Numer. Anal. 8-R2, 129 - 151 (1974).

[2] Fix, G. J., M. D. Gunzburger, and R. A. Nicolaides: Theory and applications of mixed finite element methods. In: Constructive Approaches to Mathematical Models, pp. 375 - 393.

[3] Fix, G. J. and M. Suri: The construction of stable conformating finite element for the Navier-Stokes equations by the discrete Leray process. Submitted to Numer. Math.

[4] Fix, G. J.: Hybrid finite element methods. SIAM Review 18, 3, 460 - 484 (1976).

[5] Fix, G. J., M. D. Gunzburger, and R. A. Nicolaides: On mixed finite finite element methods for first order elliptic systems. Numer. Math. 37, 29 - 48 (1981).

[6] Girault, V. and P.-A. Raviart: Finite element approximation of the Navier-Stokes equations. Springer 1979.

[7] Ladyzhenskaya, O. A.: The mathematical theory of viscous incompressible flow. Translated by R. A. Silverman, Gordon and Breach Science Publishers, 1969.

[8] Sani, R. L., P. M. Gresho, R. L. Lee, and D. F. Griffiths: The cause and cure (?) of the spurious pressures generated by certain FEM solutions of the incompressible Navier-Stokes equations: Part 1. Int. J. Num. Meth. Fluids, 1, 1, 17 - 83 (1981).

[9] Temam, R.: Navier-Stokes equations. North-Holland Publishing Co., 1977.